

# Asset GPS Tracker

**T355**



## 365 Days

Standby Time

## 2 Magnets In

Free of Installation

## IP66

Water Resistant

## Multiple Alarms

Regulate Driving Behavior

## ≤1% RMA

Quality Assurance



### 365 days' long standby time

Inbuilt high capacity battery which ensures remarkably power efficient.



### Magnetic installation

Contain two industrial magnets which facilitates it attach to flat metal surface.



### IP66 water resistant

Hard and rugged enclosure guarantees it complete shockproof and durable.



### Multiple alarms & reports

Support speeding/drop/geo-fence alarm, direction change/heartbeat report etc.



### Low rate of repairing

Less than 1% Rate of Repairing, high quality assurance and stable performance.

## Application



Container



Ship



Valuables



Vehicle

## Specifications

Item	Parameter	Specifications
Outer case	Dimension	105 mm x 75 mm x 45 mm
	Material	ABS
	Water resistance	IP66
Power consumption	Working voltage	3.7 V
	Average current	50 mA
	Standby current	0.7 mA
	Internal battery	7400 mAh/3.7 V
	Working hour	Consecutive working hours: > 120 hours Standby time: > 8760 hours
GSM	Frequency band	850/900/1800/1900 MHz
	Network	GSM/GPRS
	Antenna	Internal antenna
GPS	Speed	0.1 m/s
	Tracking sensitivity	-162 dBm
	Positioning time	Cold start < 42s, hot start < 3s, recapture time < 2s
	Positioning accuracy	10m, 2D RMS
	Satellite receiving channel	56 channels
	Antenna	Internal/External antenna
Ambient environment	Operating temperature	-15°C to 65°C
	Storage temperature	-25°C to 70°C
	Humidity	5%–95% non-condensing
Weight	322g	
Sensor	Internal acceleration sensor (used to determine movement, vibration and non-movement.)	
Memory	8 MB flash (8,192 GPRS caches and 100 SMS caches)	
LED indicator	LED indicators showing Power, GPS, and GSM status	

## Accessories

Accessories	T355 Tracker	Travel adapter	Mini USB cable	Switch sticker	CD
Optional Accessories	External GPS antenna				

## Packing data

Box size	189x150x96mm
G/W	0.8kg per box
Carton size	320X510X230mm(10 sets); 400X330X510mm(20 sets)

## Certificates

			<b>RoHS</b>
---	---	--	-------------

## Contact

Tel : +86(755)83462818      Email: info@meitrack.com  
 Fax : +86(755)83462061      Web : www.meitrack.net  
 Add: 6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd.,  
 Futian Free Trade Zone, Shenzhen, China. 518038

